



- Designed for industrial and commercial filter applications
- Heavy duty construction for maximum durability
- Various materials of construction for a wide range of process requirements
 - 316L stainless steel
 - 304L stainless steel
- Accepts Double Open End (DOE) cartridges
- Available with 1/2" 3/4" connections for easy installation.
- Ring nut closure for quick cartridge change outs
- Spring loaded knife edge seal provides positive sealing for variable length cartridges
- Supplied with mounting bracket kit and wrench
- Numerous gasket options for compatibility with most fluids

Applications

Water

Food & Beverage

Oil

Coolants

Chemicals

Electronics

Inks / Paints / Coatings

Pulp & Paper

Specifications & Operating Parameters

Maximum Operating Pressure

300 psig (20.7 bar) @ 200° F (93° C)

Connections

Inlet /Outlet: 1/2" or 3/4" FNPT

Optional: BSP

Drain: V – 1/4" NPT Plug

T – 1/4" NPT Petcock

Materials of Construction

Head / Shell: S6 316L SS / 316L SS

S4 304L SS/ 304L SS

Drain: V – SS Plug

T – Brass Petcock

Gaskets

Buna N (FDA Grade)

Optional: EPR, Silicone, Viton

Cartridge Type

DOE Cartridges