



- Designed for industrial and commercial filter applications
- Heavy duty construction for maximum durability
- Various materials of construction for a wide range of process requirements

316L stainless steel
304L stainless steel

- Accepts Double Open End (DOE) cartridges
- Available with 3/4" in-line connections for easy installation.
- Ring nut closure for quick cartridge change outs
- Spring loaded knife edge seal provides positive sealing for variable length cartridges
- Supplied with mounting bracket kit and wrench
- Numerous gasket options for compatibility with most fluids
- Flat top available for 1/4" gauge ports options

Applications

Water	Chemicals
Food & Beverage	Electronics
Oil	Inks / Paints / Coatings
Coolants	Pulp & Paper

Specifications & Operating Parameters

Maximum Operating Pressure

300 psig (20.7 bar) @ 200° F (93° C)

Connections

Inlet /Outlet: 3/4" FNPT

Optional: BSP

Drain: V – 1/4" NPT Plug

T – 1/4" NPT Petcock

Materials of Construction

Head / Shell: S6 316L SS / 316L SS

S4 304L SS/ 304L SS

Drain: V – SS Plug

T – Brass Petcock

Gaskets

Buna N (FDA Grade)

Optional: EPR, Silicone, Viton

Cartridge Type

DOE Cartridges

Custom Options

– Gauge Ports

See Ordering Guide for complete selection of options